

SHIMIZU et al., S.N. 09/406,570  
Page 2

Dkt. 2271/57219-A

### Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) An optical information recording medium comprising information tracks extending in a circumferential direction and spaced from each other in a radial direction by lands, wherein:
- a first information track and a second information track are radially adjacent but are radially spaced from each other by a single land;
  - a first phase pit encoding preformat information for a first groove in the first information track is connected to the second information track and extends radially therefrom toward, but does not reach, the first information track;
  - ~~said first phase pit and said first information track are separated radially by a partition wall;~~
  - said first phase pit and said first ~~information track~~ groove have substantially equal depths;
  - said first phase pit is radially connected with another groove adjoining on a side of the pit relative to the first groove;
  - a partition wall is formed in a radial direction between said first phase pit and said first groove;
  - obliques of the edge portions of said first phase pit are different; and
  - a track pitch of said first information track and a width and a length of said first phase pit are selected according to a condition that the preformat information for the first information track is reproduced from the first phase pit with a differential signal.

SHIMIZU et al., S.N. 09/406,570  
Page 3

Dkt. 2271/57219-A

2. (original) The optical information recording medium as defined in claim 1,  
wherein a width  $\Delta$  of said partition wall in the radial direction and the track pitch TP  
satisfy the relationship:

$$\Delta / TP \geq 0.1.$$

3. (original) The optical information recording medium as defined in claim 1,  
wherein a width  $W_p$  of said phase pit, the length  $L_p$  of said phase pit in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing  
light beam satisfy the relationship:

$$L_p/BD < 1.0, \text{ and}$$

$$0.8 \leq W_p/TP \leq 0.9.$$

4. (previously presented) The optical information recording medium as defined in claim  
1,

wherein a width  $W_p$  of said phase pit, the length  $L_p$  of said phase pit in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing  
light beam satisfy the relationship:

$$1.0 \leq L_p/BD, \text{ and}$$

$$0.5 \leq W_p/TP \leq 0.8.$$

5. (original) The optical information recording medium as defined in claim 1,

wherein a width  $W_p$  of said phase pit, the length  $L_p$  of said phase pit in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing

SHIMIZU et al., S.N. 09/406,570  
Page 4

Dkt. 2271/57219-A

light beam satisfy the relationship:

$$1.0 \leq L_p/BD, \text{ and}$$

$$0.8 \leq WP/TP \leq 0.9.$$

Claim 6 (canceled).

7. (previously presented) The method of mastering as defined in claim 18,  
wherein the values of said spot diameters BD1 and BD2 of said first and second exposing  
light beams are respectively fixed to constant values; and

wherein the distance L between the spots of said first and second exposing light beams is  
adjusted by changing the incident angle of at least one of said exposing light beams directed to an  
object lens by use of a light deflection element.

8. (currently amended) An optical information recording medium comprising:  
circumferentially extending grooves forming information tracks and phase pits forming  
circumferentially extending preformat tracks; and  
a partition wall ~~radially separating adjacent information tracks; formed in a radial~~  
direction between a phase pit for a first groove and the first groove,  
wherein said ~~grooves~~ first groove and phase ~~pits~~ pit are substantially equally deep,  
said phase ~~pits encoding preformat information for a given information track are pit is~~  
radially spaced from the connected with another groove forming the given  
information track by a partition wall adjoining on a side of the phase pit relative  
to the first groove,  
obliques of the edge portions of said phase pit are different, and

SHIMIZU et al., S.N. 09/406,570  
Page 5

Dkt. 2271/57219-A

a track pitch of said given information track and a width and a length of said phase pits are selected according to a condition that the preformat information for the given information track is reproduced from said phase pits with a differential signal.

9. (previously presented) The optical information recording medium as defined in claim 8,

wherein a width  $\Delta$  of said partition wall in the radial direction and the track pitch TP of said information track satisfy the relationship:

$$\Delta / TP \geq 0.1.$$

10. (original) The optical information recording medium as defined in claim 8,

wherein a width Wp of said phase pits, the length Lp of said phase pits in the circumferential direction, the track pitch TP of said information tracks, and a spot diameter BD of a recording/reproducing light beam satisfy the relationship:

$$Lp/BD < 1.0, \text{ and}$$

$$0.8 \leq WP/TP \leq 0.9.$$

11. (original) The optical information recording medium as defined in claim 8,

wherein a width Wp of said phase pits, the length Lp of said phase pits in the circumferential direction, the track pitch TP of said information tracks, and a spot diameter BD of a recording/reproducing light beam satisfy the relationship:

$$1.0 \leq Lp/BD, \text{ and}$$

$$0.5 \leq WP/TP \leq 0.8.$$

SHIMIZU et al., S.N. 09/406,570  
Page 6

Dkt. 2271/57219-A

12. (previously presented) The optical information recording medium as defined in claim 8,

wherein a width  $W_p$  of said phase pits, the length  $L_p$  of said phase pits in the circumferential direction of said information tracks, the track pitch  $TP$  of said information tracks, and a spot diameter  $BD$  of a recording/reproducing light beam satisfy the relationship:

$$1.0 \leq L_p/BD, \text{ and}$$

$$0.8 \leq W_p/TP \leq 0.9.$$

13. (currently amended) An optical information recording medium comprising:  
circumferentially extending grooves forming information recording tracks, and phase pits  
encoding preformat information for said tracks; and  
a partition wall formed in a radial direction between a phase pit for a first groove and the  
first groove.

wherein phase pits encoding preformat information for a given track are radially spaced  
from that track and ~~separated therefrom by a partition wall~~ and are connected to  
an adjacent track,

said ~~grooves~~ first groove and phase pits are substantially equally deep,

said phase pit is radially connected with another groove adjoining on a side of the phase  
pit relative to the first groove.

obliques of the edge portions of said phase pit are different, and

a track pitch of said given track and a width and a length of said phase pits are selected  
according to a condition that the preformat information for the given information  
track is reproduced from said phase pits with a differential signal.

SHIMIZU et al., S.N. 09/406,570  
Page 7

Dkt. 2271/57219-A

14. (original) The optical information recording medium as defined in claim 13,  
wherein a width  $\Delta$  of said partition wall in the radial direction and the track pitch TP  
satisfy the relationship:

$$\Delta / TP \geq 0.1.$$

15. (original) The optical information recording medium as defined in claim 13,  
wherein a width Wp of said phase pits, the length Lp of said phase pits in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing  
light beam satisfy the relationship:

$$Lp/BD < 1.0, \text{ and}$$

$$0.8 \leq WP/TP \leq 0.9.$$

16. (original) The optical information recording medium as defined in claim 13,  
wherein a width Wp of said phase pits, the length Lp of said phase pits in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing  
light beam satisfy the relationship:

$$1.0 \leq Lp/BD, \text{ and}$$

$$0.5 \leq WP/TP \leq 0.8.$$

17. (original) The optical information recording medium as defined in claim 13,  
wherein a width Wp of said phase pits, the length Lp of said phase pits in the  
circumferential direction, the track pitch TP, and a spot diameter BD of a recording/reproducing  
light beam satisfy the relationship:

$$1.0 \leq Lp/BD, \text{ and}$$

SHIMIZU et al., S.N. 09/406,570  
Page 8

Dkt. 2271/57219-A

$$0.8 \leq \text{WP/TP} \leq 0.9.$$

18. (currently amended) A method of mastering an optical information recording medium comprising information tracks extending in a circumferential direction and spaced from each other in a radial direction by lands, comprising:

exposing a master to a first exposing light beam for forming a first information track and a second information track that are radially adjacent but are radially spaced from each other by a single land;

exposing said master to a second exposing light beam for forming a first phase pit encoding preformat information for a first groove in the first information track, wherein said first phase pit being is connected to the second information track and extending radially therefrom toward, but not reaching, the first information track, said phase pit is radially connected with another groove adjoining on a side of the phase pit relative to the first groove, a partition wall is formed in a radial direction between said first phase pit and said first information track being separated radially by a partition wall groove, and said first phase pit and said first information track having groove have substantially equal depths;

wherein, when a spot diameter of said first exposing light beam is BD1, a spot diameter of said second exposing light beam is BD2, a distance between said first and second exposing light beams is L, and the width of said partition wall in the radial direction is  $\Delta$ , the values of BD1, BD2, L, and  $\Delta$  satisfy the relationship:

$$\Delta = L - [(BD1/2) + (BD2/2)]; \text{ and}$$

wherein a track pitch of said first information track and a width and a length of said first phase pit are selected according to a condition that the preformat information for

SHIMIZU et al., S.N. 09/406,570  
Page 9

Dkt. 2271/57219-A

the first information track is reproduced from the first phase pit with a differential  
signal.

---